

Bystronic**Bystronic Bylas 6525 BTL3500**

<b>Snijbereik/Cutting area/Schneidbereich</b>	6.500 x 2.500 mm
<b>Resonator</b>	3.500 W
<b>Bouwjaar/Year/Baujahr</b>	2000
<b>Besturing/Control/Steuerung</b>	Selectron CNC 96
<b>Ombouw/Umbau/Overhaul</b>	TouchScreen PC
<b>Wisseltafel/Changing table/Wechseltisch</b>	ja/yes/Ja
<b>Snijcapaciteit/Capacity/Kapazität</b>	St. 0,5 - 18 mm DIN 1.0037 RVS/Stainless/V2A 0,5 - 8 mm DIN 1.4301 Alu 0,5 - 6 mm DIN 3.2315
<b>Koeler/Chiller/Kühler</b>	ja/yes/Ja (Pedia)
<b>Filter/Dustcollector/Entstaubung</b>	ja/yes/Ja (Herding)
<b>Snijkoppen/Cutting head/Schneidköpfe</b>	2: 1 x 5" / 1 x 7.5"
<b>Blower/Turbine/Turbine</b>	56.000 uur/hours/Stunden
<b>Snijden/cutting/Schneiden</b>	32.000 uur/hours/Stunden
<b>Beschikbaar/available/Verfügbar</b>	Voorraad/Lager/Stock
<b>Software</b>	Optie/Optional
<b>Uitrusting/equipment/Ausstattung</b>	Bypos Reflectieabsorber/reflectionabsorber/Reflexionsabsorber Cross Jet
<b>Plaatdetectie/Blechlagedetektion/Platepositioning</b>	Automatisch/Automatik/automatic
<b>Elektrisch verbruik/electrical consumption</b>	52 kW excl. afzuiging/excl. dustcollector/ohne Absaugung
<b>Elektrische Anschlusswerte</b>	
<b>Prijs/price/Preis</b>	